

275 Series Recommended Cutting Data - Inch

Workpiece Material Group	ISO	Vc - SFM Low - High	Tool Diameter (Inch)					
			.039 - .062	.063 - .124	.125 - .188	.189 - .281	.282 - .375	.376 - .472
			Feed (in/rev)					
Low Carbon Steels	P	100 - 140	.003 - .008	.008 - .013	.008 - .016	.011 - .021	.016 - .028	.016 - .031
Medium Carbon Steels		80 - 120	.003 - .008	.008 - .013	.008 - .016	.011 - .021	.016 - .028	.016 - .031
Alloy Steels		70 - 110	.003 - .008	.008 - .013	.008 - .016	.011 - .021	.016 - .028	.016 - .031
Die / Tool Steels		50 - 90	.003 - .008	.008 - .013	.008 - .016	.011 - .021	.016 - .028	.016 - .031
Free Machining Stainless Steels	M	60 - 100	.003 - .008	.008 - .013	.008 - .016	.011 - .021	.016 - .028	.016 - .031
Austenitic Stainless Steels		30 - 60	.001 - .005	.006 - .012	.008 - .012	.008 - .016	.012 - .020	.012 - .024
Difficult Stainless Steels		20 - 50	.001 - .005	.006 - .012	.008 - .012	.008 - .016	.012 - .020	.012 - .024
PH Stainless Steels		30 - 60	.001 - .005	.006 - .012	.008 - .012	.008 - .016	.012 - .020	.012 - .024
High Temp Alloys	S	20 - 50	.0005 - .003	.004 - .008	.006 - .012	.008 - .012	.008 - .016	.010 - .018
Titanium Alloys		30 - 60	.001 - .005	.006 - .012	.008 - .012	.008 - .016	.012 - .020	.012 - .024
Gray Cast Irons	K	80 - 120	.005 - .012	.010 - .018	.014 - .026	.016 - .031	.020 - .035	.024 - .041
Ductile Cast Irons		70 - 110	.005 - .012	.010 - .018	.014 - .026	.016 - .031	.020 - .035	.024 - .041
Malleable Cast Irons		60 - 100	.005 - .012	.010 - .018	.014 - .026	.016 - .031	.020 - .035	.024 - .041
Aluminum - ≤ 10% Si	N	250 - 350	.005 - .012	.010 - .018	.014 - .026	.016 - .031	.020 - .035	.024 - .041
Aluminium - > 10% Si		200 - 300	.005 - .012	.010 - .018	.014 - .026	.016 - .031	.020 - .035	.024 - .041
Copper / Brass		180 - 250	.005 - .012	.010 - .018	.014 - .026	.016 - .031	.020 - .035	.024 - .041
Hardened Steels 45-50 HRC	H	40 - 70	.003 - .008	.008 - .013	.008 - .016	.011 - .021	.016 - .028	.016 - .031
Hardened Steels 50-55 HRC		30 - 50	.001 - .005	.006 - .012	.008 - .012	.008 - .016	.012 - .020	.012 - .024

Stock Allowance for NC Machine Reamers - Inch	
Reamer Diameter (Inch)	Total Allowance
.039 - .062	.003 - .006
.062 - .125	.005 - .009
.125 - .250	.007 - .012
.250 - .472	.010 - .015

Technical data provided should be considered advisory only as variations may be necessary depending on the particular application.

275 Series Recommended Cutting Data - Metric

Workpiece Material Group	I S O	Vc - M/Min Low - High	Drill Diameter (mm)					
			1.0 - 1.5	1.6 - 3.0	3.1 - 5.0	5.1 - 7.0	7.1 - 9.5	9.6 - 12.0
			Feed (mm/rev)					
Low Carbon Steels	P	30 - 45	.075 - .205	.205 - .330	.205 - .405	.280 - .535	.405 - .710	.405 - .785
Medium Carbon Steels		25 - 35	.075 - .205	.205 - .330	.205 - .405	.280 - .535	.405 - .710	.405 - .785
Alloy Steels		20 - 35	.075 - .205	.205 - .330	.205 - .405	.280 - .535	.405 - .710	.405 - .785
Die / Tool Steels		15 - 25	.075 - .205	.205 - .330	.205 - .405	.280 - .535	.405 - .710	.405 - .785
Free Machining Stainless Steels	M	20 - 30	.075 - .205	.205 - .330	.205 - .405	.280 - .535	.405 - .710	.405 - .785
Austenitic Stainless Steels		10 - 20	.025 - .125	.150 - .305	.205 - .305	.205 - .405	.305 - .510	.305 - .610
Difficult Stainless Steels		5 - 15	.025 - .125	.150 - .305	.205 - .305	.205 - .405	.305 - .510	.305 - .610
PH Stainless Steels		10 - 20	.025 - .125	.150 - .305	.205 - .305	.205 - .405	.305 - .510	.305 - .610
High Temp Alloys	S	5 - 15	.015 - .075	.100 - .205	.105 - .305	.205 - .305	.205 - .405	.255 - .455
Titanium Alloys		10 - 20	.025 - .125	.150 - .305	.205 - .305	.205 - .405	.305 - .510	.305 - .610
Gray Cast Irons	K	25 - 35	.125 - .305	.255 - .455	.355 - .660	.405 - .785	.510 - .890	.610 - 1.040
Ductile Cast Irons		20 - 35	.125 - .305	.255 - .455	.355 - .660	.405 - .785	.510 - .890	.610 - 1.040
Malleable Cast Irons		20 - 30	.125 - .305	.255 - .455	.355 - .660	.405 - .785	.510 - .890	.610 - 1.040
Aluminum - ≤ 10% Si	N	75 - 105	.125 - .305	.255 - .455	.355 - .660	.405 - .785	.510 - .890	.610 - 1.040
Aluminium - > 10% Si		60 - 90	.125 - .305	.255 - .455	.355 - .660	.405 - .785	.510 - .890	.610 - 1.040
Copper / Brass		55 - 75	.125 - .305	.255 - .455	.355 - .660	.405 - .785	.510 - .890	.610 - 1.040
Hardened Steels 45-50 HRC	H	10 - 20	.075 - .205	.205 - .330	.205 - .405	.280 - .535	.405 - .710	.405 - .785
Hardened Steels 50-55 HRC		10 - 15	.025 - .125	.150 - .305	.205 - .305	.205 - .405	.305 - .510	.305 - .610

Stock Allowance for NC Machine Reamers - Metric	
Reamer Diameter (mm)	Total Allowance
1.0 - 1.5	.08 - .15
1.5 - 3.0	.13 - .23
3.0 - 6.0	.18 - .30
6.0 - 12.0	.25 - .38

**If you don't see
the size you need -
Contact Customer
Service for
assistance.**

Safety Note
Always wear the appropriate personal protective equipment such as safety glasses and protective clothing when using solid carbide or HSS cutting tools. Machines should be fully guarded.

WARNING: This product can expose you to chemicals including cobalt which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Technical data provided should be considered advisory only as variations may be necessary depending on the particular application.